



# Static Oil Separator Dimensions / Light Liquid Separator with Modules/ Lamellar Pack coalescence Refill filter

Article Code	Range NS (lt/sec)	Sludge Load Volume (mc)	Separator water Volume (lt)	Light liquids storage capacity (lt)	Oil separator External Dimensions (cm)	Pipes Diameter (mm)	Tank Weight (ql)	Cover slab weight (ql)		
								h. 10 cm (B125)	h. 15 cm (C250)	h. 20 cm (D400)
DISCE1C-FC	1	0,30	581	407	125X130XH100	125	11,8	4,0	6,1	8,1
DISCE1,5C-FC	1,5	0,45	1466	422	125X130XH150	125	15,6	4,0	6,1	8,1
DISCE2C-FC	2	0,60	2127	608	125X180XH150	125	19,6	5,6	8,4	11,2
DISCE3C-FC	3	0,90	3116	887	175X180XH150	125	23,8	7,8	11,7	15,6
DISCE4-8C-FC	4-8	2,40	3928	1341	180X240XH150	160	47,1	10,7	16,1	21,5
DISCE4Y8C-FC	4-8	2,40	4214	967	180X180XH200	160	51,2	8,0	12,1	16,1

DISCE10A-PL	10	1,00	6400	600	180X270XH200	200	63,9	9,8	14,8	19,7
DISCE10B-PL	10	2,00	7168	672	180X300XH200	200	77,4	13,4	20,1	26,8
DISCE10C-PL	10	3,00	7680	720	180X320XH200	200	80,8	14,3	21,5	28,6
DISCE20A-PL	20	2,00	6989	672	180X300XH200	250	77,4	13,4	20,1	26,8
DISCE20B-PL	20	4,00	8736	840	180X370XH200	250	89,3	16,5	24,8	33,1
DISCE20C-PL	20	6,00	9984	960	180X420XH200	250	97,7	18,8	28,2	37,6
DISCE30A-PL	30	3,00	11752	848	246X270XH250	250	109,4	16,5	24,7	33,0
DISCE30B-PL	30	6,00	14102	1017	246X320XH250	250	120,6	19,6	29,3	39,1
DISCE30C-PL	30	9,00	16453	1187	246X370XH250	250	131,7	22,6	33,9	45,2
DISCE40A-PL	40	4,00	13560	1017	246X320XH250	300	126,5	19,6	29,3	39,1
DISCE40B-PL	40	8,00	15820	1187	246X370XH250	300	137,8	22,6	33,9	45,2
DISCE40C-PL	40	12,00	18080	1356	246X420XH250	300	149,2	25,7	38,5	51,3
DISCE50A-PL	50	5,00	13628	1017	246X320XH250	300	125,1	19,6	29,3	39,1
DISCE50B-PL	50	10,00	18170	1356	246X420XH250	300	147,4	25,7	38,5	51,3
DISCE50C-PL	50	15,00	20442	1526	246X470XH250	300	164,0	28,7	43,1	57,4
DISCE60A-PL	60	6,00	13696	1017	246X320XH250	300	125,1	19,6	29,3	39,1
DISCE60B-PL	60	12,00	18261	1356	246X420XH250	300	147,4	25,7	38,5	51,3
DISCE60C-PL	60	18,00	22826	1695	246X520XH250	300	175,2	31,8	47,7	63,6
DISCE70A-PL	70	7,00	20747	1526	246X470XH250	300	164,0	28,7	43,1	57,4
DISCE70B-PL	70	14,00	25357	1865	246X570XH250	300	186,4	34,8	52,2	69,7
DISCE70C-PL	70	21,00	29968	2204	246X670XH250	300	208,7	40,9*	61,4*	81,9*
DISCE80A-PL	80	8,00	23165	1695	246X520XH250	300	175,2	31,8	47,7	63,6
DISCE80B-PL	80	16,00	27798	2034	246X620XH250	300	197,6	37,9*	56,8*	75,8*
DISCE80C-PL	80	24,00	32431	2373	246X720XH250	300	225,4	44,0*	66,0*	88,0*
DISCE90A-PL	90	9,00	23278	1695	246X520XH250	300	175,2	31,8	47,7	63,6
DISCE90B-PL	90	18,00	27934	2034	246X620XH250	300	197,6	37,9*	56,8*	75,8*



DISCE90C-PL	90	27,00	34917	2543	246X770XH250	300	236,5	47,1*	70,6*	94,1*
DISCE100A-PL	100	10,00	24176	1865	246X570XH250	400	186,4	34,8	52,2	69,7
DISCE100B-PL	100	20,00	28572	2204	246X670XH250	400	208,7	40,9*	61,4*	81,9*
DISCE100C-PL	100	30,00	35166	2712	246X820XH250	400	247,7	50,1*	75,2*	100,2*
DISCE120A-PL	120	12,00	24363	1865	246X570XH250	400	186,4	34,8	52,2	69,7
DISCE120B-PL	120	24,00	31007	2373	246X720XH250	400	225,4	44,0*	66,0*	88,0*
DISCE120C-PL	120	36,00	43155	3221	246X970XH250	400	286,7	59,3*	88,9*	118,5*
DISCE150A-PL	150	15,00	31434	2373	246X720XH250	400	225,4	44,0*	66,0*	88,0*
DISCE150B-PL	150	30,00	42661	3221	246X970XH250	400	286,7	59,3*	88,9*	118,5*
DISCE150C-PL	150	45,00	55108	4068	246X570XH250 + 246X670XH250	400	163,9+ 208,7	34,8+ 40,9*	52,2+ 61,4*	69,7+ 81,9*
DISCE200A-PL	200	20,00	42165	3051	246X920XH250	400	270,1	56,2	84,3	112,4
DISCE200B-PL	200	40,0	58562	4238	246X520XH250 + 246X770XH250	400	152,7+ 236,5	31,8+ 47,1	47,7+ 70,6	63,6+ 94,1
DISCE200C-PL	200	60,0	74960	5424	246X720XH250 + 246X920XH250	400	202,8+ 270,1	44,0+ 56,2	66,0+ 84,3	88,0+ 84,3

\* Cover Slab divided into two parts  
The data reported is purely indicative